Safety Data Sheet

A490 SKID Penetrant/Lubricant



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: SKID Penetrant/Lubricant

Product Code: A490

Product Use: Mold Release

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols







GHS Classification

Gases under pressure - Liquified Gas Aspiration Hazard Category 1 Flammable Aerosol Category 2 Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Carcinogenicity Category 2

Reproductive Toxicity Category 2

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word Danger

Hazard Statements Flammable aerosol.

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor/....

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell. Specific treatment (see ... on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS#	Percent
Hydrocarbon propellant	68476-86-8	20 - 40
solvent naphtha (petroleum), heavy aliph.	64742-96-7	1-20
Distillates (petroleum), hydrotreated light	64742-47-8	1-20
Xylene	1330-20-7	1-20
Petroleum hydrocarbon	64742-47-8	1-20
Ethyl benzene	100-41-4	1-20
Organic oil	8002-09-3	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 2 Flammability: 4 Physical: 1 Personal See Section 8
Protective

Equipment:

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: For liquid contact, treat for frostbite if necessary. In case of contact, immediately wash contaminated area with plenty of water for

at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not induce vomiting. Have

victim drink 8 to 10 ounces of water to dilute the material in the stomach. Contact a physician, medical facility, or poison control

center immediately. Aspiration into the lungs can cause serious damage.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and

quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

Inhalation of high concentrations of the material, or one of it's components, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that

are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources

at locations distant from the material's handling point.

Fire Fighting Instructions:

Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Water is generally not effective and may spread fire; however, water spray may be

used from a safe distance to cool closed containers and protect surrounding area. Do not direct a solid stream of

water or foam into hot burning pools, this may cause frothing and increase fire intensity.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Remove all sources of ignition. Ventilate contaminated area. If runoff occurs, notify authorities as required. Wear appropriate clothing.

^{*} See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Use

with adequate ventilation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. This material can be harmful or irritating. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Wash hands thoroughly after handling.

Use bonding and grounding when transferring quantities of material.

Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 120 degrees F. Store away Storage:

from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or

bases). Keep away from heat, sparks and flame. Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from

known, suspected or apparent adverse effects). Ventilation is required to maintain operator exposure below published

exposure limits. Local exhaust should be used in areas where exposure limits may be exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin.

Respiratory Protection: If respiratory irritation develops below the recommended exposure limits, use an NIOSH approved nuisance

dust/mist/organic vapor respirator. A supplied air respirator should be used if ventilation is not sufficient to maintain

exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

COMPONENT Hydrocarbon propellant	<u>CAS</u> # 68476-86-8	ACGIH TLV 1000ppm	OSHA PEL Not established	OTHER Not established
solvent naphtha (petroleum), heavy aliph.	64742-96-7	Not established	Not established	Not established
Distillates (petroleum), hydrotreated light	64742-47-8	100 ppm	500 ppm	Not established
Xylene	1330-20-7	150 PPM STEL; 651 MG/M3 STEL	Not established	100ppm
Petroleum hydrocarbon	64742-47-8	5 mg/m3 (oil mist)	Not established	Not established
Ethyl benzene	100-41-4	100ppm TWA	100ppm TWA	100ppm 10 hr-TWA (NIOSH)
Organic oil	8002-09-3	Not established	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Lower Flammability Limit (%): Not applicable Aerosol can Appearance: Clear with yellow tint Upper Flammability Limit (%): Not applicable Odor: Petroleum solvent 46.00 Vapor Pressure (PSIG @ 70°F): Vapor Density [air = 1]: Odor Threshold: Slight >1 Not applicable Relative Density (H2O=1): 0.83

Melting/Freezing Point (°F): No data available Solubility in Water: Not determined Boiling Point (°F): No data available Partial Coefficient: n-No data available

octanol/water:

Not applicable Autoignition Temperature (°F): Not applicable Flash Point (°F PMCC): Evaporation Rate: Not determined Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available No data available Viscosity, dynamic (cSt):

Percent VOCs (%): 40 - 60

10. STABILITY AND REACTION

Chemical Stability:

Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Avoid contact with: Strong Conditions to Avoid:

oxidizing agents. Chlorine. Hypochlorites. Strong acids. Strong bases. Open flames and high temperatures.

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Aldehydes. Various

hydrocarbons. Polymer fragments.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental

No data available.

Toxicity:

IngredientCAS #Toxicological DataHydrocarbon propellant68476-86-8No data available

Inhalation LC50 (4h) Rat 658 mg/L
Distillates (petroleum), hydrotreated light 64742-47-8 Dermal LD50 Rabbit > 2000 mg/kg

Oral LD50 Rat > 5000 mg/kg

Xylenes 1330-20-7 Dermal LD50 Rabbit > 2000 mg/kg

Oral LD50 Rat = 5000 mg/kg INHALATION LC50 Rat 5000 ppm

NJ Trade Secret Registry #80100382-5007P Dermal LD50 Rabbit > 8000 mg/kg

Oral LD50 Rat 8639 mg/kg

Inhalation LC50 (4h) Rat > 5 mg/L Ethyl benzene 100-41-4 Dermal LD50 Rabbit = 15433 mg/kg

No data available

Inhalation LC50 Mouse = 6 mg/L

 Organic oil
 8002-09-3
 Dermal LD50 Rabbit > 2000 mg/kg

 Oral LD50 Rat = 3200 mg/kg

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available Mobility: No data available Degradability: No data available.

Ingredient CAS # Toxicological Data

Distillates (petroleum), hydrotreated light 64742-47-8 96HR LL50 Rainbow Trout 2 mg/L

48HR EL50 Daphnia 1.4 mg/L 72HR EL50 Algae 1 mg/L

Xylene 1330-20-7 Aquatic LC50 (96h) MINNOW 24 - 30 mg/L

Aquatic LC50 (24h) Daphnia 100 - 1000 mg/L #80100382-5007P Aquatic LC50 (96h) MINNOW 24500 mg/L

48 HR EC50 Daphnia = 21000 mg/L Ethyl benzene $100\text{-}41\text{-}4 \qquad \qquad \text{Aquatic LC50 (96h) Rainbow Trout} = 8.4 \text{ mg/L}$

48HR EC50 Daphnia = 9.55 mg/L 72HR EC50 Algae 4.9 mg/L

Organic oil 8002-09-3 Aquatic LC50 (96h) Rainbow Trout 18 mg/L

48HR EC50 Daphnia 24 mg/L 72HR EC50 Algae > 15 mg/L

13. DISPOSAL CONSIDERATIONS

NJ Trade Secret Registry

Disposal: Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

^{† &}quot;Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

 COMPONENT
 CAS #
 % BY WEIGHT
 Regulatory Body

 Xylene
 1330-20-7
 1-20
 SARA Section 313

 Ethyl benzene
 100-41-4
 1-20
 SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

 Ethyl benzene
 100-41-4
 1-20
 Prop65 Cancer

 Benzene
 71-43-2
 0.001- 0.01
 Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

 Toluene
 108-88-3
 0.01 - 0.1
 Prop65 Birth Defects

 Benzene
 71-43-2
 0.001- 0.01
 Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Other Information: MSDS Prepared by L. Dean Swartz, MSDS Coordinator

Version Date: 10/13/15

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.